

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 November 2004 (18.11.2004)

PCT

(10) International Publication Number
WO 2004/099495 A1

- (51) International Patent Classification⁷: **D21F 5/02** (74) Agent: **FORSSÉN & SALOMAA OY**; Eerikinkatu 2, FI-00100 Helsinki (FI).
- (21) International Application Number: **PCT/FI2004/000271** (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: **5 May 2004 (05.05.2004)**
- (25) Filing Language: **Finnish**
- (26) Publication Language: **English**
- (30) Priority Data:
20030691 **8 May 2003 (08.05.2003)** **FI**
- (71) Applicant (for all designated States except US): **METSO PAPER, INC.** [FI/FI]; Fabianinkatu 9 A, FI-00130 Helsinki (FI).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **RAJALA, Pasi** [FI/FI]; Hehtokatu 9 C 6, FI-20540 Turku (FI). **HAVUKAINEN, Robert** [FI/FI]; Haapakallionkuja 1 D 13, FI-05460 Hyvinkää (FI). **KORHONEN, Ville** [FI/FI]; Ritoniementie 4, FI-40250 Jyväskylä (FI). **ELIKOJ, Seppo** [FI/FI]; Keskussairaalantie 16, FI-40600 Jyväskylä (FI). **AHONEN, Pasi** [FI/FI]; Valimontie 69, FI-40530 Jyväskylä (FI). **SALMINEN, Martti** [FI/FI]; Rautpohjankatu 3 B 48, FI-40700 Jyväskylä (FI). **JUPPI, Kari** [FI/FI]; Hiekkapohjantie 259, FI-40270 Palokka (FI). **KEKKO, Pasi** [FI/FI]; Kontinperänpolku 120, FI-41660 Toivakka (FI).
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
- with international search report
 - before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **METHOD FOR CONTROL OF THE CURL OF PAPER IN THE TREATMENT OF SURFACE-SIZED PAPER, AND FINISHING SECTION OF A PAPER MACHINE**

(57) Abstract: The invention relates to a method in the treatment of surface-sized paper, in particular fine paper, in a finishing section of a paper machine. In the method a paper web (W) is first dried in a forward dryer section (D) of the paper machine in several successive downward open drying groups (G₁...G₆) that apply single-wire draw, after which the paper web (W) is finished in the finishing section. In the finishing section the web (W) is surface-sized in a surface-sizing unit (20) and dried. According to the invention, in the method, the surface-sized paper web (W) is mainly dried by means of contact-free drying. The web (W) is dried at least partly by means of airborne web-dryers (31, 32, 34, 36) or by means of impingement drying. In the method, the power of the airborne web-drying/impingement drying is regulated on both sides of the web (W) such that the tendency of curling created in the web (W) in the forward dryer section (D) can be controlled. In addition, the invention relates to a finishing section of a paper machine in the treatment of surface-sized paper, in particular fine paper, in the paper finishing section. Before the finishing section, the paper machine comprises a forward dryer section (D) in which there are several successive downward open drying groups (G₁...G₆) that apply single-wire draw. The finishing section comprises surface-sizing devices (20) and drying means. According to the invention, the drying means of the finishing section are mainly based on contact-free drying. At least one of the means are airborne web-dryers/impingement dryers (31, 32, 35, 36), whose power can be regulated such that the tendency of curling of the web can be controlled by the effect of drying applied on the different sides of the web (W).

WO 2004/099495 A1